



DCS-F5602S 2MP VANDAL-RESISTANT FIXED DOME NETWORK CAMERA

KEY FEATURES

OPTICS

- Day/Night Functionality
- SmartIR, up to 30 m (98 ft) IR Distance
- Car-grade LEDs, Brighter and Uniform Light Compensation
- 2D/3D DNR (Digital Noise Reduction)

COMPRESSION

- Ultra 265, H.264, MJPEG
- Embedded Smart Algorithm
- Triple Streams
- 9:16 Corridor mode


NETWORK

- ONVIF Conformance

STRUCTURE

- Wide Temperature Range: -35°C to 60°C (-31°F to 140°F)
- Wide Input Voltage Range of ±25%
- IP67
- 2-Axis
- IK10

DIMENSIONS



Camera					
Sensor	1/2.9", progressive scan, 2.0 megapixel, CMOS				
Lens	2.8 mm@F2.0				
DORI Distance	Lens	Detect(m)	Observe(m)	Recognize(m)	Identify(m)
	2.8mm	45	18	9	4.5
	4mm	64.3	25.7	12.9	6.4
Angle of View (H)	109.9°				
Angle of View (V)	56.7°				
Angle of View (O)	142.9°				
Adjustment Angle	Pan: 0°~360°				
Shutter	Auto/Manual, 1~1/100000 s				
Minimum Illumination	Colour: 0.005 Lux (F2.0, AGC ON) 0 Lux with IR				
Day/Night	IR-cut filter with auto switch (ICR)				
Digital Noise Reduction	2D/3D DNR				
S/N	>52dB				
IR Range	Up to 30m (98 ft) IR range				
Defog	Digital Defog				
WDR	DWDR				
Video					
Video Compression	Ultra 265, H.264, MJPEG				
H.264 Code Profile	Baseline profile, Main Profile, High Profile				
Frame Rate	Main Stream:2MP (1920×1080): Max. 30 fps; Sub Stream:2MP (1920×1080): Max. 30 fps; Third Stream:D1 (720×576): Max. 30 fps				
HLC	Supported				
BLC	Supported				
9:16 Corridor Mode	Supported				
OSD	Up to 8 OSDs				
Privacy Mask	Up to 8 areas				
ROI	Up to 8 areas				
Motion Detection	Up to 4 areas				
Smart					
Behavior Detection	Intrusion, cross line, motion detection				
Intrusion	Enter and loiter in a pre-defined virtual region				
Cross Line	Cross a pre-defined virtual line				
Motion Detection	Moving within a pre-defined virtual region				
Recognition	Face detection, Audio detection				
Intelligent Identification	Defocus, Scene Change, Object Left, Object Moving				
Statistical Analysis	People counting				
General Function	Watermark, IP Address Filtering, Tampering Alarm, Access Policy, ARP Protection, RTSP Authentication, User Authentication				
Storage					
Edge Storage	Micro SD, up to 256 GB				
Network Storage	ANR				
Network					
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP				
Compatible Integration	ONVIF(Profile S, Profile G, Profile T), API				
Interface					
Network	1 RJ45 10M/100M Base-TX Ethernet				
General					
Power	12 V DC±25%, PoE (IEEE802.3 af) Power consumption: Max 4W				
Dimensions (Ø x H)	Ø108.5 x 81 mm (Ø4.28" x 3.2")				
Weight	0.35 kg (0.77 lb)				
Working Environment	-35°C ~ +60°C (-31°F ~ 140°F), Humidity :10%~95% RH(non-condensing)				
Ingress Protection	IP67				
Vandal Resistant	IK10				