

# 86 X 86 ANGLED CLIP TYPE FACEPLATES



Overview shall follow

## KEY FEATURES

- UL94 V-0 flame test for ABS
- EU Directive 2011/65/EU (RoHS-2)
- UL Listed

## SPECIFICATIONS

### 1-2 port UK Style fFaceplates

Jack Compatibility	Shielded or Unshielded RJ45 Keystone Jacks CAT5e
Category Compatibility	CAT6 CAT6A
Mount Type	Wall or Ducts
Shuttered	Optional
Color	White (other colors available)
Insertion Method	Back Loading

Material	ABS, UL94V-0
Operating temperature	-10 to + 60°C at 10-90% RH (non condensing)
Storage temperature	-40 to + 68°C

## ORDERING INFORMATION

PART CODE	DESCRIPTION
DSC-FBTLOF1SQHU2	86*86mm faceplate angled , wo/ shutter, 1 port
DSC-FBTLOF2SQHU2	86*86mm faceplate angled , wo/ shutter, 2 port
DSC-FBTLOF1SQHS2	86*86mm faceplate angled , w/ shutter, 1 port
DSC-FBTLOF2SQHS2	86*86mm faceplate angled , w/ shutter, 2 port
DSC-FBTL000SQ	Single-gang Back box ,86*86*37mm