CAT5e FTP OUTDOOR CABLES



Enhanced performance cable for transmission of high speed data, digital and analogue voice and video (RGB) signals on LANs. Supports Gigabit Ethernet (1000 baseT) standard. Operates at bandwidth of 100MHz.

This cable well exceeds the requirements of TIA/EIA-568-C.2 and ISO/IEC 11801

ELECTRICAL PROPERTIES

KEY FEATURES

conductivity

PE insulation

drain wire

UV PVC Outer Jacket

Comply with Cat5e specifications 4-pair shielded twisted pair (FTP) cable 24 AWG solid copper conductor for superior

Pairs are wrapped in aluminum foil with

Packaged in MDF spool in a box

Characteristic Impedance: $100\pm15\Omega$ Conductor Resistance: $\leq 9.38\Omega/100m$ Mutual Capacitance: <5.6nF/100m Resistance Unbalance: 5% Max Capacitance Unbalance: 330pF/100m Delay Skew: < 45ns NVP: 69%

SPECIFICATIONS

Conductor: 24 AWG Solid bare Copper (4 pair)

Insulation: High Density Polyethylene

Pairs: 2 Insulated conductors twisted together

Sheath: **UV PVC Outer sheath** Shield: Aluminum/Polyester Foil

Cable Diameter: 6.3 mm nominal

ORDERING INFORMATION

PART CODE	DESCRIPTION
NCB-5EF0BLR-305	Cat5e FTP 24 AWG UV PVC Outdoor

Cable-305m/Roll, Black Colour

COLOUR CODE

PAIR NO.	COLOUR
1-2 3-6 4-5 7-8	White/Orange Stripe and Orange White/Green Stripe and Green White/Blue Stripe and Blue White/Brown Stripe and Brown

