D-Link Category 6 Modular Plugs are suitable for both 24-26 AWG stranded and solid cables. This modular design means they can be used for a wide range of networking needs that span across a whole business system, eliminating the need to constantly switch between plugs when cabling. Compatible with standard RJ45 Wire network crimping tools, D-Link CAT6 modular plugs fit seamlessly into any well-established standard operating procedure, making cable assembly easy.

KEY FEATURES

- Fits 24-26 AWG
- Reliable and fast connection
- 50 micro-inch thick gold plating
- Polycarbonate housing

SPECIFICATIONS

UTP Modular Plugs

RJ45 Jack Housing & Insert: PC, UL94V-2 RJ45 Jack Contact Terminal Material: Phosphor bronze

RJ45 Jack Contact Terminal Finish: 50 micro-inch gold plating

Operating Temperature: -40 °C to 80°C

FTP Modular Plugs:

PC, UL94V-2 RJ45 Jack Housing & Insert:

RJ45 Jack Contact Terminal Material: Phosphor bronze with 100 micro-inch

nickel plating on contact area

RJ45 Jack Contact Terminal Finish: 50 micro-inch gold plating

Insertion Cycles: 2000 times

RJ45 Jack Shield: Bronze with Nickel plating

-40°C to 125°C Operating Temperature:

ORDERING INFORMATION

PART CODE	DESCRIPTION
NPG-5E1TRA501-100	Cat5e UTP Modular Plugs (100 Units/Pack)
NPG-C61TRA501-100	Cat6 UTP Modular Plugs (100 Units/Pack)
NPG-C61MET502-100	Cat6 FTP Modular Plugs (100 Units/Pack)