

# CAT6 FTP KEYSTONE JACKS



D-Link Category 6 keystone jacks are RJ45 8P 8C 50u jacks suitable for 22-26 AWG stranded and solid wire, tool-less and compatible with both 110 & Krone punch down tool. They are capable of re-termination. They are available in universal labels colour-coded for T568A and T568B wiring schemes and fit in high density keystone patch panel. It supports IEC 60603-7- 4 and complied with ANSI/TIA/EIA-568-C.2 standard.

Contact Resistance: 100 milliohms

## KEY FEATURES

- RJ45 8P 8C 180° 50u Punch Down Jack
- Terminating 4 Pairs, 22-26 AWG Cable, stranded and solid wire
- Universal labels colour-coded for T568A and T568B wiring schemes
- Fitting high density keystone panel

## SPECIFICATIONS

RJ45 Jack Shield:	Bronze with Nickel
RJ45 Jack:	Housing: Zinc Alloy Contact Bracket: PC, UL 94V-2 Transparent Colour
RJ45 Jack Contact:	Material: Phosphor Bronze with Nickel Plated Finish: 50 micro-inch Gold plated on Plug Contact area
IDC:	Housing: PC, UL94V-2 Terminal: Phosphor Bronze with Tin plated
IDC CAP:	Zinc Die-Casting, Nickel-Plated

## ORDERING INFORMATION

PART CODE	DESCRIPTION
-----	
NKJ-C6SMET2B21	Cat6 FTP 180° Tool Less Keystone Jack-Metallic