

CAT6 LSZH PATCH CORDS



D-Link Cat6 patch cords are high-quality four pair twisted stranded cable terminated with RJ45 modular plugs at both the ends. It complies to the TIA/EIA-568-C. 2 standard. These patch cords are appropriate for high-speed data transmissions.

SPECIFICATIONS

Conductor:	24 AWG Multi-strands
Conductor Metal:	Bare Copper
Insulation:	High Density Polyethylene
Material:	LSZH
Heat Resistance:	60°C minimum (Temperature Limited)
Flame Property:	The purpose of the vertical flame test is to screen out flammable wires. It follows the VW-1(UL)and FT-1 (CSA) Insertion
Cycles:	750 times

APPLICATION

- 10BASE-T, 100BASE-TX Fast Ethernet, 1000BASE-T
- 100VG-AnyLAN (IEEE802.12)
- 500MHz Broadband Video
- Voice, T1, ISDN
- 155/622 Mbps ATM
- Power over Ethernet (PoE)

MODULAR CONNECTOR / PLUG

RJ45 Jack Contact

Material:	Phosphor Bronze with Nickel Plated
Finish:	50 micro-inch Gold plated
Temperature Range:	-10° ~ 80°C
Dielectric withstanding voltage:	500V AC
Insulation Resistance:	35M Ohm (max.)

ORDERING INFORMATION

PART CODE	DESCRIPTION
NCB-C6UGRYR1-1-LS	Cat6 UTP 24AWG Patch Cord, LSZH, 1M
NCB-C6UGRYR1-2-LS	Cat6 UTP 24AWG Patch Cord, LSZH, 2M
NCB-C6UGRYR1-3-LS	Cat6 UTP 24AWG Patch Cord, LSZH, 3M