

CAT5e SHIELDED PATCH PANELS



KEY FEATURES

- Eight-port RJ45 modules applied
- ID stripes for identifying port allocations
- IDC compatible with Krone tool
- Terminating 4 pairs, 22-26 AWG, shielded cable
- Friendly installation, right angle between IDCs and RJ45 Keystone jacks
- Jack shutter to keep dust away
- Hand screw, easy to open cover

D-Link Category 5e shielded patch panels are eight port RJ45 modules applied and suitable for 22-26AWG stranded and solid wire, compatible with Krone punch down tools. D-Link patch panels have improved Cable Management with optional Cable Management bar terminating 4 pairs UTP cable. They are complied with the **ANSI/TIA/EIA-568-C.2** standard.

SPECIFICATIONS

Identification:	I.D. Plate: PVC. Transparent Colour Paper
Panel:	SPCC. 1.2 mm thickness with Black (RAL 9005) Colour painted
RJ45 Jack:	Housing: PBT+15%GF, UL 94V-0.
RJ45 Jack Contact:	Material: Phosphor Bronze Finish: 3mm 50 micro-inch Gold plated over nickel plated
IDC:	Terminal: Phosphor Bronze with Tin plated
Dust Cover:	PC, UL 94V-0, Transparent Black (RAL 9004) colour
Ground wire:	18AWG wire, with green/yellow striped colour, length 40cm

ORDERING INFORMATION

PART CODE	DESCRIPTION
NPP-5E2BLK241	Cat5e Shielded 24 Port Loaded Patch Panel
NPP-5E2BLK481	Cat5e Shielded 48 Port Loaded Patch Panel