

CAT6 0.5U LOADED PATCH PANELS



D-Link Category 6 0.5U patch panels are eight port RJ45 modules applied and suitable for 22-26AWG stranded and solid wire, compatible with both 110 & Krone punch down tools. D-Link patch panels have improved Cable Management with optional Cable Management bar terminating 4 pairs UTP cable. They are complied with the ANSI/TIA/EIA-568-C.2 standard.

KEY FEATURES

- Eight-port RJ45 modules applied
- High Density 24 port 0.5U patch panel
- IDC compatible with 110 & Krone tool
- Terminating 4 pairs, 22-26 AWG, stranded and solid wire
- Ideal for limited rack space solutions

SPECIFICATIONS

Panel:	SPCC. 1.5 mm thickness with Black (RAL 9005) Colour painted
RJ45 Jack:	Housing: PBT+GF,UL 94V-0, Contact brackets: PBT+GF,UL94V-2
RJ45 Jack Contact:	Material: Phosphor Bronze with nickel plating Finish: 50 micro-inch Gold plated on plug contact area
IDC:	Housing:PC+GF,UL94V-2, Terminal: Phosphor Bronze with Tin plated
Dust Cover:	PC, UL 94V-0

ORDERING INFORMATION

PART CODE	DESCRIPTION
NPP-C61BLK243	Cat6 Unshielded 24 Port Loaded Patch Panel-0.5U