

CAT6 LOADED ANGLED PATCH PANELS



D-Link Category 6 angled patch panels are six port RJ45 modules applied and suitable for 22-26AWG stranded and solid wire, compatible with both 110 & Krone punch down tools. D-Link patch panels have improved Cable Management with optional Cable Management bar terminating 4 pairs UTP cable. They are complied with the ANSI/TIA/EIA-568-C.2 standard.

KEY FEATURES

- Six-port RJ45 modules applied
- ID stripes for identifying port allocations
- IDC compatible with 110 & Krone tool
- Terminating 4 pairs, 22-26 AWG, stranded and solid wire
- Designed to easily route cables into vertical cable managers
- Reduces the need for horizontal, front cable management bars

SPECIFICATIONS

Identification:	I.D. Plate: PVC. Transparent Colour Paper
Panel:	SPCC. 1.5 mm thickness with Black Colour painted Housing: PBT + GF,UL 94V-0.
RJ45 Jack:	Material: Phosphor Bronze with Nickel plated Finish: 50 micro-inch Gold plated over nickel plated
RJ45 Jack Contact:	Housing: PC +GF,UL 94 V-2,Terminal: Phosphor Bronze with Tin plated ABS, UL 94V-0
IDC:	SPCC,1.5mm thickness,painted in black
Back Cover:	
Support wire:	

ORDERING INFORMATION

PART CODE	DESCRIPTION
NPP-C61BLK242	Cat6 Unshielded Angled 24 Port Loaded Patch Panel