CAT6 UTP PATCH PANELS



D-Link Category 6 patch panels are six port RJ45 modules applied and suitable for 22-26AWG stranded and solid wire, compatible with both 110 & Krone punch down tools. D-Link patch panels have improved Cable Management with optional Cable Management bar terminating 4 pairs UTP cable. They are complied with the ANSI/TIA/EIA-568-C.2 standard.

KEY FEATURES

- Six-port RJ45 modules applied
- ID stripes for identifying port allocations
- IDC compatible with 110 & Krone tool
- Terminating 4 pairs, 22-26 AWG, unshielded cable
- Improved cable management with an optional cable management bar (Simple type, or "T" slot type)
- Universal labels Colour-coded for T568A and T568B wiring schemes

SPECIFICATIONS

Identification: I.D. Plate: PC, Transparent color with paper

Panel: SPCC. 1.6 mm thickness with Black (RAL 9005) Colour painted

RJ45 Jack: Housing: PBT+ Glass Fiber UL94V-0

Contact Bracket: PBT+Glass Fiber, UL94V-0, Black Color

RJ45 Jack Contact: Material: Phosphor Bronze with Nickel plated

Finish: 50 micro-inch Gold plated on Plug contact area

IDC: Housing: PC, UL94V-2

Terminal: Phosphor Bronze with Tin plated

Jack Bracket Set: ABS

Support Bar: SPCC, 1.6 mm thickness with

Black (RAL 9005) Colour painted

ORDERING INFORMATION

PART CODE DESCRIPTION

NPP-C61BLK241 Cat6 UTP 24 Port Loaded Patch Panel
NPP-C61BLK481 Cat6 UTP 48 Port Loaded Patch Panel

https://me.dlink.com/ AltraNET Product Guide | **D-Link**