

CAT6A FTP KEYSTONE JACKS



D-Link Category 6A FTP keystone jacks are RJ45 8P 8C 50u Jacks suitable for 22-24 AWG stranded and solid wire, tool-less and compatible with both 110 & Krone punch down tools. They fit in high density keystone patch panel. Compliant with TIA/EIA 568A and B.

KEY FEATURES

- RJ45 8P 8C 180° 50u Punch Down Jack
- Terminating 4 Pairs, 22-26 AWG Cable, stranded and solid wire
- Universal labels colour-coded for T568A and T568B wiring schemes
- Fitting high density keystone panel

SPECIFICATIONS

RJ45 Jack Shield:	Bronze with Nickel
RJ45 Jack:	Housing: Zinc Alloy Contact Bracket: PC, UL 94V-2 Transparent Colour
RJ45 Jack Contact:	Material: Phosphor Bronze with Nickel Plated Finish: 50 micro-inch Gold plated on Plug Contact area
IDC:	Housing: PC, UL94V-2 Terminal: Phosphor Bronze with Tin plated
IDC CAP:	Zinc Die-Casting, Nickel-Plated

ORDERING INFORMATION

PART CODE	DESCRIPTION
NKJ-6ASMET2B21	Cat6A FTP 180° Tool-Less Keystone Jack-Metallic