

CAT5e UTP PATCH CORDS



D-Link CAT5e UTP Patch Cords are high-quality four-pair twisted stranded cables terminated with RJ45 modular plugs at both the ends. It is as per the TIA/EIA-568-C.2 standard. These patch cords are appropriate for high speed data transmission.

APPLICATION

- 10BASE-T, 100BASE-TX Fast Ethernet, 1000BASE-T (IEEE802.3)
- 100VG-AnyLAN (IEEE802.12)
- 500MHz Broadband Video
- Voice, T1, ISDN
- 155/622 Mbps ATM
- Power over Ethernet (PoE)

SPECIFICATIONS

Conductor:	24 AWG, Multi-strands
Conductor Metal:	Bare Copper
Insulation Material:	High Density Polyethylene
Material:	PVC UL94V-0
Heat Resistance:	60°C minimum (Temperature limited)
Flame Property:	The purpose of the vertical flame test is to screen out flammable wires. It follows the VW-1 (UL) and FT-1 (GA) standards
Insertion Cycles:	750 times

MODULAR CONNECTOR / PLUG

RJ45 JACK CONTACT

Material:	Phosphor Bronze with Nickel Plated
Finish:	50 micro-inch Gold plated
Temperature Range:	-10 ~ 80°C
Dielectric withstanding voltage:	500V AC
Insulation Resistance:	35M Ohm (max.)

ORDERING INFORMATION

PART CODE	DESCRIPTION
NCB-5EUGRYR1-05	Cat5e UTP 24AWG Patch Cord, 0.5m, Grey
NCB-5EUBLUR1-1	Cat5e UTP 24AWG Patch Cord, 1m, Blue
NCB-5EUBLUR1-2	Cat5e UTP 24AWG Patch Cord, 2m, Blue
NCB-5EUBLUR1-3	Cat5e UTP 24AWG Patch Cord, 3m, Blue
NCB-5EUGRYR1-5	Cat5e UTP 24AWG Patch Cord, 5m, Grey
NCB-5EUGRYR1-10	Cat5e UTP 24AWG Patch Cord, 10m, Grey
NCB-5EUGRYR1-15	Cat5e UTP 24AWG Patch Cord, 15m, Grey