

CAT6A SHIELDED PATCH CORDS



D-Link Cat6A shielded patch cords are high quality four pair twisted stranded cable terminated with RJ45 modular plugs at both the ends. It is compliant to the TIA/EIA 568C.2 standard. These patch cords are appropriate for high speed data transmission.

SPECIFICATIONS

Conductor:	26 AWG, Multi-cores
Conductor Metal:	Bare Copper
Insulation Material:	HD-PE
Material:	PVC
Colour Code:	Grey
Heat Resistance:	75°C minimum (Temperature limited)

ORDERING INFORMATION

PART CODE	DESCRIPTION
NCB-6ASGRYR1-1	Cat6A Shielded 26AWG Patch Cord, 1M, Grey
NCB-6ASGRYR1-2	Cat6A Shielded 26AWG Patch Cord, 2M, Grey
NCB-6ASGRYR1-3	Cat6A Shielded 26AWG Patch Cord, 3M, Grey

APPLICATION

- 10BASE-T, 100BASE-TX Fast Ethernet, 1000BASE-T, 10GBASE-T (IEEE802.3)
- 100VG-AnyLAN (IEEE802.12)
- 500MHz Broadband Video
- Voice, T1, ISDN
- 155/622 Mbps ATM
- Power over Ethernet (PoE)

MODULAR CONNECTOR / PLUG

RJ-45 8P for transparent Colour	
Gold Plated:	50U"
Contact Blade	Phosphor Bronze
Dielectric withstanding voltage:	500V AC
Insulation Resistance:	35M Ohm (max.)
UL Applications:	250V AC, PC UL94-V-2