


CAT6A UTP PATCH CORDS



D-Link Cat6A patch cords are high quality four pair twisted stranded cable terminated with RJ45 modular plugs at both the ends. It is TIA/EIA-568-C.2 standard. These patch cords are appropriate for high speed data transmission.

SPECIFICATIONS

Conductor:	24 AWG Multi-strands
Conductor:	Bare Copper
Insulation:	HD-PE
Material:	PVC
Colour Code:	Grey
Heat Resistance:	60°C minimum (Temperature limited)
Flame Property:	The purpose of the vertical flame test is to screen out flammable wires. It follows the VW-1 (UL) and FT-1 (CSA) standards
Cycles:	750 times

ORDERING INFORMATION

PART CODE	DESCRIPTION
NCB-6AUGRYR1-1	Cat6A UTP 24AWG Patch Cord, 1M, Grey
NCB-6AUGRYR1-2	Cat6A UTP 24AWG Patch Cord, 2M, Grey
NCB-6AUGRYR1-3	Cat6A UTP 24AWG Patch Cord, 3M, Grey

*Available in other colors and lengths on requests

APPLICATION

- 10BASE-T, 100BASE-TX Fast Ethernet, 1000BASE-T, 10GBASE-T (IEEE802.3)
- 100VG-AnyLAN (IEEE802.12)
- 500MHz Broadband Video
- Voice, T1, ISDN
- 155/622 Mbps ATM
- Power over Ethernet (PoE)

MODULAR CONNECTOR / PLUG

RJ45 Jack Contact	
Material:	Phosphor Bronze with Nickel Plated
Finish:	50 micro-inch Gold plated
Temperature Range:	-10 ~ 80°C
Dielectric withstanding voltage:	500V AC
Insulation Resistance:	35M Ohm (max.)