

CAT6 FTP FAST TERMINATION KEYSTONE JACKS



8P8C Shielded RJ45 Fast Termination Keystone Jacks

Frequency Range:	1-250 MHz
Compatible Conductors:	22-24 AWG
Pin-Pair Assignment:	T568A & T568B
Contacts:	Phosphor Bronze Alloy Plated with 50 micro-inch of Gold
Shield:	Die-cast Metal Case
Housing:	Zinc-alloy Fully Shielded

KEY FEATURES

- Support PoE++ application
- UL Listed
- Optimizing the NEXT in both ends on a channel.
- It is terminated by a Punch-Down Tool or a Fast-Termination Tool
- Compatible for 24-port applications in 1U blank patch panel
- Easily snap in and out of patch panel, and surface boxes or other application.
- RoHS Compliant.

SPECIFICATIONS

Orientation:	180°
Termination Blocks:	110 IDC (Phosphor Bronze Alloy Plated with 100 micro-inch 100% Sn Alloy)
Insertion/Withdrawal:	750 cycles
Cable Re-Termination:	20 cycles
Operating Temperature:	-20 to +60oC at 5-95% RH (non condensing)
Ampacity:	1.5 A max.
Contact Resistance:	20 mOhm max.
DC Resistance:	0.1 Ohm max.
Voltage Rating:	75 Vdc max.
Insulation Resistance:	500 MegaOhm min. @100 Vdc
Tools:	Fast Termination Tool or Punch Down Tool
Compatible with 24-port & 48-port 1U panels	

ORDERING INFORMATION

PART CODE	DESCRIPTION
DSC-KJFTC62SVB	Cat.6 FTP Fast Termination Jack (4PPoE, 2A)