

CAT6 UNSHIELDED FAST TERMINATION ANGLED KEYSTONE JACKS



8P8C Unshielded RJ45 Fast Termination Keystone Jacks

| | |
|------------------------|---|
| Frequency Range: | 1-250 MHz |
| Compatible Conductors: | 22-24 AWG |
| Pin-Pair Assignment: | T568A & T568B |
| Contacts: | Phosphor Bronze Alloy Plated with 50 micro-inch of Gold |
| Shield: | None |
| Housing: | High impact FR compound, UL 94V-0 |
| Standard Color: | White |

KEY FEATURES

- Angled Keystone Jack increases rack density and reduces the need for horizontal cable management systems.
- It works with DSC-PPFTUN1BK12 blank patch panel.
- It is terminated by a Punch-Down Tool or a Fast-Termination Tool.

SPECIFICATIONS

| | |
|------------------------|--|
| Orientation: | 180° |
| Termination Blocks: | 110 IDC (Phosphor Bronze Alloy Plated with 100 micro-inch 100% Sn Alloy) |
| Insertion/Withdrawal: | 750 Cycles |
| Cable Re-Termination: | 20 Terminations |
| Operating Temperature: | -20 to +60oC at 5-95% RH (non-condensing) |
| Ampacity: | 1.5 A max |
| Contact Resistance: | 20 mOhm max |
| DC Resistance: | 0.1 Ohm max |
| Voltage Rating: | 75 Vdc max |
| Insulation Resistance: | 500 MegaOhm min. @100 Vdc |
| Tools: | Fast Termination Tool or Punch Down Tool |

Compatible with DSC-PPFTUN1BK12 Blank Patch Panel

ORDERING INFORMATION

| PART CODE | DESCRIPTION |
|-----------------|--|
| DSC-KJFTC61WHBA | Cat.6 UTP Fast Termination Jack Angled |