

UNSHIELDED FAST TERMINATION KEYSTONE JACKS



KEY FEATURES

- It is terminated by a Punch-Down Tool or a Fast-Termination Tool
- Support PoE++ application

8P8C unshielded RJ45 fast termination keystone jacks

Frequency Range:	1-500 MHz
Compatible Conductors:	22-24 AWG
Pin-Pair Assignment:	T568A & T568B
Contacts:	Phosphor Bronze Alloy Plated with 50 micro-inch of Gold
Shield:	None
Housing:	High impact FR compound
Standard Color:	White/Black (other colors available)

SPECIFICATIONS

Orientation:	180°
Termination Blocks:	110 IDC(Phosphor Bronze Alloy Plated with 100 micro-inch 100% Sn Alloy)
Insertion/Withdrawal:	750 cycles
Cable Re-Termination:	20 cycles
Operating Temperature:	-20 to +60oC at 5-95% RH (non-condensing)
Ampacity:	1.5 A max.
Contact Resistance:	20 mOhm max.
DC Resistance:	0.1 Ohm max.
Voltage Rating:	75 Vdc max.
Insulation Resistance:	500 MegaOhm min. @100 Vdc
Tools:	Fast Termination Tool or Punch Down Tool

Compatible with 24-port & 48-port 1U panels

ORDERING INFORMATION

PART CODE	DESCRIPTION
DSC-KJFT6A1WHB	Cat.6A UTP Fast Termination Jack, White
DSC-KJFT6A1BLB	Cat.6A UTP Fast Termination Jack, Blue
DSC-KJFT6A1RDB	Cat.6A UTP Fast Termination Jack, Red
DSC-KJFT6A1YLB	Cat.6A UTP Fast Termination Jack, Yellow
DSC-KJFT6A1GRB	Cat.6A UTP Fast Termination Jack, Green
DSC-KJFT6A1BKB	Cat.6A UTP Fast Termination Jack, Black
DSC-KJFT6A1ORB	Cat.6A UTP Fast Termination Jack, Orange