



5G CPE Router



Experience 5G connection speeds up to 4.6 Gbps (theoretical value) and high-speed Wi-Fi up to 3.0 Gbps (theoretical value) on all your connected devices throughout your home.

DWR-2000M

- Next generation 5G connectivity speeds up to 4.6 Gbps (theoretical value)
- Built-in Wi-Fi AX3000 distributes high-speed, high-performance Wi-Fi to all your connected devices
- Dual-band Wi-Fi with MU-MIMO technology makes 4K streaming, VR gaming or video chatting a breeze
- 2.5 Gigabit Ethernet WAN/LAN port and 2.5 Gigabit Ethernet LAN port
- Connect up to 64 devices to your home Wi-Fi network
- Latest Wi-Fi security with 128-bit encryption



4.67 Gbps / 2.5 Gbps High-speed 5G Internet

Connect with next-generation 5G speeds up to 4.6 Gbps (theoretical value) and experience lightning-fast downloads, lower latency and reduced congestion



Dual-Band AX3000

2400 Mbps (5 GHz) + 600 Mbps (2.4 GHz) - Plenty of bandwidth for video streaming, cloud storage, social media, and downloading



2.5 Gigabit Ethernet Ports

High-speed connections for wired devices and wired broadband



Up to 64 Devices

Connect all of your home's Wi-Fi devices to share a single broadband connection



SIM Slot

Simply insert your SIM card to share your mobile broadband connection throughout the home

IPv6

Supports IPv6

Future-proof and compatible with the next generation of Internet standards

Technical Specifications		/ DWR-2000M
Hardware Parameters		
Device Interfaces	1 x 10/100/1000/2500 Gigabit Ethernet LAN Port, 1 x 10/100/1000/2500 Mbps Gigabit Ethernet WAN/ LAN port, 1 x USB Type C Port, 1 x LTE SIM/USIM Slot, 1 x Reset Hole, 1 x WPS Button, 1 x Power Port, 1 x RJ11	
LED	Power, WLAN, 4G LTE, 5G	
Antenna Type	2 x 3dBi Internal 2.4G & 5G Dual Band Antenna, Internal 4G/5G Antennas	
Wi-Fi Data Rate (theoretical value)	2T2R 2.4GHz 802.11b/g/n / ax, 574 Mbps 2T2R 5.8GHz 802.11a/n/ac/ax, 2402 Mbps @ 160Mhz	
Wireless IEEE Standard	802.11a/b/g/n/ac/ax	
WAN Interface	DHCP Static IP PPPoE (PPPoE Pass-through)	
Functionality		
Security Protocol	WEP (128bits), 802.11i 128-bit TKIP/AES	
Firewall	DoS , IP/MAC Address Filtering	
Software		
Device Management	Web UI	
Physical		
Hardware version	B1	
Size	(L*W*H) 107*107*185mm	
Weight	690g	
Power Input	12 V 2 A	
Operating Temperature	-10 to 40 °C	
Storage Temperature	-40 to 70 °C	
Operating Humidity	10% to 90% non-condensing	
Certifications	CE , RoHS	
Band Frequency		
5GNR Sub6 GHz	N1/3/5/7/8/20/28/38/n40/41/77/78	
LTE Cat20 FDD	LTE FDD: B1/B3/B5/B7/B8/B20/B28/B32	
LTE Cat20 TDD	LTE TDD:B38/B40/B41/B42/B43	
WCDMA	B1, B5, B8	
Order Information		
DWR-2000M HW. B1	5G AX3000 CPE Router	