

Highlights

Fast Mobile Broadband for All Your Devices

Connect your high-speed mobile broadband connection to multiple Wi-Fi devices such as smartphones, tablets, PCs, and more

Security Features

Uses a built-in firewall and industry-standard WPA/WPA2 security protocols to help keep your data safe from prying eyes

Go Anywhere

The DWR-932M is small enough to fit in your pocket, and its rechargeable battery means you're not tied to a wall outlet



DWR-932M

4G/LTE Mobile Router

Features

Connectivity

- Uses a USIM card to connect to the Internet
- Compatible with 802.11b/g/n wireless devices
Wireless Frequency Range: 2.4Ghz- 2.4835Ghz
EIRP: 18.7 dBm
- Micro-USB port for easy charging

Portability

- Up to five hours of battery in one charge so you stay connected longer
- Small size lets you drop it in a purse or pocket and take it wherever you go

Security

- WPA/WPA2 Wi-Fi security protocols for industry-standard encryption
- Built-in firewall helps keep unwanted connections out
- Wi-Fi Protected Setup (WPS) for one-touch setup

The DWR-932M 4G/LTE Mobile Router is a 4G LTE Cat4 high-speed broadband wireless WAN (WWAN) to Wi-Fi mobile hotspot. The DWR-932M uses a 4G Internet connection to give you an easy-to-set-up Wi-Fi network anywhere you need one. Instead of limiting your mobile Internet connection to a single device through a USB dongle, the DWR-932M allows you to create a Wi-Fi hotspot to share your connection with multiple Wi-Fi devices. The convenient size means you can share your connection anywhere; use it in a cafe to send e-mail while your friend reads the news, or at the airport so you and your coworkers can work while waiting for your plane.

Connect Anywhere

Simply insert your data-enabled SIM card to set up your very own mobile Wi-Fi network. The DWR-932M is perfect for when you need to quickly set up an impromptu network; it's ideal for business trips when you need to share an Internet connection with everybody during a meeting, or use it for travel, allowing you to provide all your travel companions with Internet access.

Security Features Help Protect Your Network

The DWR-932M 4G/LTE Mobile Router is easy-to-use and includes a host of security features. The built-in firewall helps your network resist intrusions over the Internet, while WPA encryption helps prevent unauthorized users from connecting to your network. Wi-Fi Protected Setup (WPS) allows you to quickly add new devices at the touch of a button, getting you connected in no time.

Flexible Usage

The DWR-932M 4G/LTE Mobile Router gives you instant connectivity, all in a powerful yet pocket-sized device. The rechargeable 2100 mAh Li-ion battery allows you to stay connected for long periods of time. Plug-and-play with no complicated software to install, getting online with the DWR-932M 4G/LTE Mobile Router is quick, easy, and convenient.

Technical Specifications

General

Frequency Support	<ul style="list-style-type: none"> FDD-LTE: Band 1/3/5/7/8/20 TDD-LTE: Band 38/40 	<ul style="list-style-type: none"> UMTS/HSDPA/HSUPA: 2100/900 MHz GSM/GPRS/EDGE: 900/1800 MHz
Data Throughput	<ul style="list-style-type: none"> Downlink up to 150 Mbps 	<ul style="list-style-type: none"> Uplink up to 50 Mbps
Security	<ul style="list-style-type: none"> WPA/WPA2 PSK Auto (TKIP/AES) 	<ul style="list-style-type: none"> WPS Push-Button Connection
Advanced Functions	<ul style="list-style-type: none"> Built-in firewall Built-in NAT 	<ul style="list-style-type: none"> UPnP

Physical

Interfaces	<ul style="list-style-type: none"> 802.11n/g/b wireless LAN Standard mini-SIM card interface 	<ul style="list-style-type: none"> Micro-USB port
Antenna	<ul style="list-style-type: none"> Internal LTE antenna 	<ul style="list-style-type: none"> Internal Wi-Fi antenna
LED	<ul style="list-style-type: none"> Power Status SMS Status 	<ul style="list-style-type: none"> Wi-Fi Status Cellular Signal Strength
Power	<ul style="list-style-type: none"> DC 5V/1 A ± 5% 	<ul style="list-style-type: none"> 2100 mAh Li-ion battery
Dimensions	<ul style="list-style-type: none"> 59 x 98 x 15.5mm 	
Weight	<ul style="list-style-type: none"> 86.04g 	
Operating Temperature	<ul style="list-style-type: none"> -10 to 60°C 	
Storage Temperature	<ul style="list-style-type: none"> -30 to 80°C 	
Operating Humidity	<ul style="list-style-type: none"> 5% to 65% (non-condensing) 	
Certifications	<ul style="list-style-type: none"> CE 	<ul style="list-style-type: none"> RoHS