



NKJ-C6BLU1B21



NKJ-C6GRN1B21



NKJ-C6WHI1B21



NKJ-C6YEL1B21



NKJ-C61RED1B21

Cat6 UTP Keystone Jacks

FEATURES

- RJ45 8P 8C 180°C 50u Punch Down Jack
- Terminating 4 pairs, 22-26 AWG Cable
- Universal labels color coded for T568A and T568B wiring schemes
- Fitting high density keystone panel
- UL, ETL, RoHS certified

SPECIFICATIONS

- RJ45 Jack:
 Housing: PC, UL94V-0 with Option Color
 Contact Bracket: PC, UL94V-0 Transparent Colour
- RJ45 Jack Contact:
 Material: Phosphor Bronze with Nickel Plated
 Finish: 50 micro-inch Gold plated on Plug Contact area
- IDC:
 Housing: PC,UL94V-0
 Terminal: Phosphor Bronze with Tin plated
- 4. IDC CAP: PC, UL94V-0
- 5. PCB: FR4, UL 94V-0

PERFORMANCE

- T568A & T568B wiring sticker
- Insertion force: 20N max (IEC 60603-7-4)
- Retention strength: 7.7 kg between jack and plug
- Operation temperature: -10°C to 60°C (ISO/IEC 11801, ANSI/TIA/EIA 568 C.2)
- Life (Mating Cycles):
 Jack: 750 cycle min (ISO/IEC 11801, IEC 60603-7-4)
- IDC: suitable for 22-26 AWG stranded and solid wire, compatible with both 110 & Krone punch down tools
- The Cat6 transmission performance is in compliance with the ANSI/TIA/EIA 568 C.2 standard

Product No.	Description	Color
NKJ-C6WHI1B21	Cat6 UTP Keystone Jack	White
NKJ-C6BLU1B21	Cat6 UTP Keystone Jack	Blue
NKJ-C6RED1B21	Cat6 UTP Keystone Jack	Red
NKJ-C6GRN1B21	Cat6 UTP Keystone Jack	Green
NKJ-C6YEL1B21	Cat6 UTP Keystone Jack	Yellow

ABS: Acrylonitrile Butadiene Styrene